

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
6 May 2004 (06.05.2004)

PCT

(10) International Publication Number
WO 2004/036990 A1

- (51) International Patent Classification⁷: A01M 1/20
- (21) International Application Number:
PCT/EP2003/011825
- (22) International Filing Date: 24 October 2003 (24.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/281,087 25 October 2002 (25.10.2002) US
- (71) Applicant (for all designated States except US): BASF AKTIENGESELLSCHAFT [DE/DE]; , 67056 Ludwigshafen (DE).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): KLEIN, Clark, D., Jr. [US/US]; 96 Double Oak Drive, Pittsboro, NC 27312 (US); DAVIES, David, M. [ZA/US]; 101 Tidbury Court, Raleigh, NC 27615 (US).
- (74) Agent: KINZEBACH, Werner; Patentanwälte, Reitstötter, Kinzebach & Partner (GbR), Sternwartstr. 4, 81679 München (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TERMITE-MONITORING DEVICE AND ASSOCIATED METHOD



(57) Abstract: A camouflaged termite-monitoring device is provided. Such a device comprises a housing (100) which defines a cavity (300) and an opening (400). A perforated bait cartridge (475) is disposed within the cavity and contains a bait material (450) adapted to be attractive to termites. A mesh-like member (500) is operably engaged with the housing so as to cover the opening and to retain the bait cartridge in the cavity. The mesh-like member is further adapted to allow termites to pass therethrough into the cavity and the bait cartridge and to infiltrate the housing. An inspection hatch (550) is operably engaged with the housing and is configured to allow visual inspection of the bait cartridge within the cavity from outside the housing. Such a visual inspection is performed without removing the housing from engagement with the upper ground surface. An associated method is also provided.

BEST AVAILABLE COPY

WO 2004/036990 A1

TERMITE-MONITORING DEVICE AND ASSOCIATED METHOD

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a device and method for detecting termites and, more particularly, to a termite-monitoring device and associated method.

5 Description of Related Art

Subterranean termites are major insect pests and a bane to homeowners throughout the country. A significant amount of money is spent annually by homeowners to repair termite damage and/or to obtain the necessary termite control treatments. In many instances, the homeowners are not aware of catastrophic termite infestations, or
10 even the presence of termites, until major damage becomes evident or the damage is found in a home inspection by a home inspector or pest control professional. However, such inspections are generally only performed annually by pest control professionals, and usually only if the homeowner has entered a termite protection contract. Termites, on the other hand, may infest a home at any time and an infestation may cause significant
15 damage to wooden structures on the premises in a very short period of time. Thus, even with a termite protection contract, a home may suffer significant damage if a termite infestation is not immediately detected and eradicated.

There exist some products that are configured to be implanted into the ground around the premises and contain a bait having an active ingredient that is toxic to
20 termites. However, such products do not readily permit the homeowner to determine if termites are even present on the premises. For example, such products must often be removed from the ground in order for the homeowner to determine if the bait has been consumed. In addition, the product may be covered with mud or otherwise affected by

moisture in the ground, which may make it difficult for an untrained homeowner to see the bait, much less determine if the bait has been consumed by termites. Further, in some instances, the products may be easily covered by debris such as leaves or soil, whereby the products may readily become forgotten or overlooked by the homeowner if the
5 homeowner is not diligent about regular monitoring of the products. On the other hand, if the products are made to be readily located by the homeowner, such products may often undesirably stand out in a common residential landscape or be otherwise unsightly on the premises.

Thus, there exists a need for an unobtrusive termite monitoring device for
10 allowing expedient detection, by the homeowner, of the presence of termites on the property, which would thereby permit the homeowner to contact a pest control professional to inspect and treat the premises with an appropriate insecticide to eradicate the termites and prevent damage, or further damage, to wooden structures on the premises.

15

BRIEF SUMMARY OF THE INVENTION

The above and other needs are met by the present invention which, in one embodiment, provides a camouflaged termite-monitoring device. Such a device comprises a housing configured as a landscape element and adapted to engage an upper
20 ground surface, wherein the housing defines a cavity and an opening to the cavity through a ground-contacting surface of the housing. A perforated bait cartridge is configured to fit within the cavity and contains a bait material adapted to be attractive to termites. A mesh-like member is operably engaged with the housing about the ground-contacting portion so as to cover the opening and to retain the bait cartridge in the cavity.
25 The mesh-like member is further adapted to allow termites attracted by the bait material to pass therethrough into the cavity and the bait cartridge and to infiltrate the housing. An inspection hatch is operably engaged with the housing and is configured to allow visual inspection of the bait cartridge from outside the housing. Such a visual inspection will reveal whether termites have infiltrated the housing and consumed the bait material,
30 and is performed without removing the housing from engagement with the upper ground surface.

Another advantageous aspect of the present invention comprises a method of monitoring for termites at a site. First, a housing configured as a landscape element is engaged with an upper ground surface without implanting the housing in the ground, wherein the housing defines a cavity and an opening to the cavity through a ground-
5 contacting surface of the housing. The cavity has a perforated bait cartridge disposed therein, wherein the bait cartridge contains a bait material adapted to be attractive to termites. The housing has a mesh-like member operably engaged therewith about the ground-contacting surface so as to cover the opening and to retain the bait cartridge in the cavity. The mesh-like member is further adapted to allow termites attracted by the bait
10 material to pass therethrough into the cavity and the bait cartridge and to infiltrate the housing. The bait cartridge is then inspected to determine whether termites have infiltrated the housing and have consumed the bait material, without removing the housing from engagement with the ground, wherein at least one of the bait cartridge, the cavity, and the mesh-like member are configured so as to become increasingly
15 prominently visible through the inspection hatch as the bait material is consumed.

Thus, embodiments of the present invention meet the above-identified needs and provide distinct advantages as further detailed herein.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

20 Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1 is a schematic illustration of a residential landscape illustrating several termite monitoring devices according to embodiments of the present invention;

FIG. 2 is a schematic illustration of a termite monitoring device, in engagement
25 with an upper ground surface, according to one embodiment of the present invention;

FIG. 3 is a schematic illustration of a termite monitoring device, separated from the upper ground surface, according to one embodiment of the present invention;

FIG. 4 is a schematic assembly drawing of a termite monitoring device according to one embodiment of the present invention; and

30 **FIGS. 5A and 5B** are schematic illustrations of a termite monitoring device according to an alternate embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present inventions now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of the invention are shown. Indeed, these inventions may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these
5 embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout.

FIGS. 1-4 schematically illustrate a termite monitoring device according to one embodiment of the present invention, the device being indicated generally by the numeral
10 **10**. Such a device **10** comprises a housing **100** extending from a ground-contacting surface **200** and defining a cavity **300** therein. The ground-contacting surface **200** further defines an opening **400** for providing access to the cavity **300**. A bait material **450** is disposed within a bait cartridge **475** which, in turn, is capable of being disposed within the cavity **300**. The bait cartridge **475** is secured and retained within the cavity **300** by a
15 mesh-like member **500** operably engaged with the housing **100** and covering the opening **400**. An inspection hatch **550** is operably engaged with the housing **100** so as to permit a visual inspection of the bait cartridge **475** from outside the housing **100**, without removing the housing **100** from engagement with the upper surface **5** of the ground.

The housing **100** may be configured in a variety of shapes and formed of a variety
20 of materials. In some particularly advantageous embodiments of the present invention, the housing **100** is configured as a landscape element, wherein such an element is preferably unobtrusive or otherwise natural in a residential setting and thus camouflaged with respect to items commonly found in a residential yard. For example, as shown in **FIG. 1**, the housing **100** may be configured as a rock, a log, a paving or stepping stone, a
25 brick, a border element for a flowerbed or the like, a decorative figurine, or any other item capable of incorporating the various aspects of the present invention as described herein. Moreover, such a housing **100** is preferably adapted to be deployed and used at the upper ground surface **5**. That is, the housing **100** is preferably configured such that the user is not required to implant the housing **100** in or under the upper ground surface **5**,
30 which minimizes the effort required from the user for deploying the device **10**. However, one skilled in that art will appreciate that, in some instances, the user may have to prepare

the upper ground surface 5 for receiving the device 10, wherein the extent of the preparations may depend on the configuration of the device 10. For instance, where the housing 100 is configured as a stepping stone, a brick, or a border element, the upper ground surface 5 may have to be leveled or otherwise dug out to some extent in order for the housing 100 to be seated level and upright with respect to the upper ground surface 5. Where the housing 100 is configured as a decorative figurine, log, or rock, it may be sufficient to just place the housing 100 in the desired position at a selected spot on the upper ground surface 5.

In some instances, the device 100 may also be provided, when and if necessary, with an anchor element 50 configured to secure the housing 100 to the ground 5, as shown in FIGS. 2 and 3. The anchor element 50 may be, for example, integral with the housing 100, attached thereto by a bracket (not shown) or a tether (not shown), or otherwise operably engageable with the housing 100.

The ground-contacting surface 200 of the housing 100 comprises a surface of the housing 100 contacting the upper ground surface 5 when the device 10 is deployed in its intended orientation. That is, the ground-contacting surface 200 may be considered the "bottom surface" of the device 10, in many instances. Accordingly, the ground-contacting surface 200 may comprise, for example, the bottom surface of a decorative figurine, a flat surface of a stepping stone, a brick, or a border element, the base of a vase, or the like. The ground-contacting surface 200 further defines an opening 400 into the cavity 300 in the housing 100. The opening 400 is generally sufficient for the bait cartridge 475 to be inserted therethrough into the cavity 300. However, in some instances, the housing 100 may define an additional opening (not shown) or, for example, may be configured to have separate engageable portions which may be disengaged in order to insert the bait cartridge 475 into the cavity 300 and then re-engaged to contain the bait cartridge 475. The bait cartridge 475 may be comprised of, for example, a thin plastic or metal mesh, wherein the mesh may be configured so as to allow termites and other wood-destroying insects to be able to proceed through the mesh into the interior of the bait cartridge 475, while the mesh may also be configured to selectively prohibit other insects from passing therethrough. In some instances, the bait cartridge 475 may be formed in the shape of a rectangle, though other suitable shapes are to be considered

within the spirit and scope of the present invention. In some embodiments, the bait material 450 is sealed within the bait cartridge 475, wherein the bait cartridge 475 is intended as a disposable and replaceable unit.

For example, as shown in **FIGS. 2 and 4**, the housing 100 may further include
5 an inspection hatch 550 configured with respect to the housing 100 such that the bait cartridge 475 within the cavity 300 may be viewed from outside of the housing 100 through the hatch 550. For example, the hatch 550 may be disposed on an upper surface of the housing 100, generally opposite to the ground-contacting surface 200, such that, when the device 10 is deployed, the user is able to open and look through the hatch 550
10 without removing the device 10 from the upper ground surface 5. Preferably, the hatch 550 is opaque, or at least semi-opaque, and is comprised of the same material as the housing 100 so as to present an integral appearance, or is configured to appear as an appropriate component of the housing 100. In still other instances, the hatch 550 may also be configured to be, for example, removable, hinged, or otherwise removably
15 engaged with respect to the housing 100 so as to allow access to the cavity 300 from above the upper ground surface 5 without requiring the device 10 to be removed from the upper ground surface 5. In this manner, the hatch 550 may be opened or removed to inspect the bait cartridge 475 within the cavity 300 and/or to replace the bait cartridge 475 within the cavity 300. For example, as shown in **FIGS 5A and 5B**, the housing 100
20 may be configured with a first portion 110 configured to engage the upper ground surface 5 and a second portion 120 operably engaged with the first portion 110, wherein the first and second portions 110, 120 cooperate to define the cavity 300 and the second portion 120 may be regarded as essentially comprising the hatch 550. The first and second portions 110, 120 may be, for example, removable, hinged, or otherwise removably
25 engaged with respect to each other. As shown, one or more hinges 130 may connect the first and second portions 110, 120, while a latch 140 may removably secure the first and second portions 110, 120 together opposite the hinge 130. The latch 140 may then simply be undone so as to allow the second portion 120 to be rotated away from the first portion 110 about the hinge 130 and the bait material 450 within the bait cartridge 475 to
30 be inspected.

In one embodiment of the present invention, the bait material 450 is preferably selected so as to be attractive to, for example, termites or other wood-destroying insects. In one advantageous embodiment, the bait material 450 is at least partially comprised of, for example, aspen wood fibers or aspen wood having a fibrous texture. Further, the bait material 450, according to some embodiments of the present invention, is non-toxic to termites and other wood-destroying insects. Accordingly, one advantageous aspect of the present invention is that, when deployed, the device 10 is configured to allow termites or other wood-destroying insects to enter the cavity 300 and the bait cartridge 475 through the mesh-like member 500, wherein consumption of the bait material 450 may then be observed or monitored through the hatch 550 without removing the housing 100 from the upper ground surface 5, or through the mesh-like member 500 if the housing 100 is removed from the upper ground surface 5. Accordingly, if consumption of the bait material 450 is observed, such an observation may be reported to a central station (not shown) comprising the manufacturer of the device 10 or an entity otherwise associated with or authorized by the manufacturer of the device 10. The central station may then, for example, notify or dispatch a pest control professional to the residence or may direct that other pest control procedures may be undertaken before the occurrence of damage to wooden structures on the property. However, in some instances, certain bait cartridges 475 may be available having a bait material 450 with an active ingredient toxic to termites and other wood-destroying insects as will be appreciated by one skilled in the art. Such bait cartridges 475 with a toxic bait material 450 may be provided by the central station or pest control professional or may otherwise be available for replacement in the housing 100 of the bait cartridge 475 having the non-toxic bait material 450. In still other instances, a device 10 according to embodiments of the invention may be initially provided with a bait cartridge containing a toxic bait material 450.

One skilled in the art will further appreciate that the bait cartridge 475 containing the bait material 450 may also be formed, as necessary, to facilitate insertion thereof into the cavity 300 through the opening 400 and/or through the hatch 550. In some instances, the device 10 may be configured to be disposable or replaceable, in that the device 10 may be provided with the bait cartridge 475, or just the bait material 450, already deposited in the cavity 300, wherein neither the mesh-like member 500 nor the hatch 550

can be opened to remove or replace the bait material 450 and/or the bait cartridge 475. As such, in such instances, if and when the bait material 450 is depleted, the device 10 may be discarded, replaced with another, or merely left in place as a landscape element.

5 The mesh-like member 500, as shown in FIGS. 2-4, is operably engaged with the ground-contacting surface 200 of the housing 100 so as to be in contact or at least in close proximity with the upper ground surface 5 when the device 10 is installed as a landscape element or, in some instances, when the housing 100 is just rested on the upper ground surface 5 in an upright position, as in the case of a decorative figurine. As such, when the device 10 is deployed, the bait material 450 may be in contact with the upper
10 ground surface 5, or otherwise in close proximity thereto, through the bait cartridge 475 and the mesh-like member 500. The mesh-like member 500 may also be hinged, removable, or otherwise removably engaged, with respect to the housing 100, but also configured to cover the opening 400 when in a locked position. The mesh-like member 500 is further configured to define openings 525 therein, with the openings 525 being
15 sized to permit the targeted termites and/or other wood-destroying insects to enter the cavity 300 therethrough. However, according to one aspect of the present invention, the openings 525 and/or the mesh-like member 500 are further configured to exclude other non-targeted insects, which may also be attracted to the bait material 450, from entering the cavity 300 and the bait cartridge 475, consuming the bait material 450, and providing
20 a false indication of the presence of the termites or the other wood-destroying insects.

In some instances, the bait material 450 is more attractive to termites or other wood-destroying insects when wet. Accordingly, according to one advantageous aspect of the present invention, the bait material 450 may also be configured to be self-wicking so as to extract moisture from, for example, the ground or the atmosphere, when the
25 device 10 is deployed. In other instances, as shown in FIG. 4, the device 10 may further include a water reservoir 600 operably engaged with the housing 100 and configured to provide continuous, or at least substantially continuous, wetting of the bait material 450.

According to yet another advantageous aspect of the present invention, the bait cartridge 475, the cavity 300, the mesh-like member 500, or other portions of the housing
30 100 may be configured to become increasingly prominently visible through the hatch 550 as the bait material 450 becomes consumed by termites or other wood destroying insects.

For example, the interior surface of the housing 100 defining the cavity 300 and/or the mesh-like member 500 and/or the bottom surface of the bait cartridge 475 may be, for instance, brightly colored. Initially, when the bait cartridge 475 is first inserted in the cavity 300, the brightly colored cavity surface, bottom surface of the bait cartridge 475, and/or mesh-like member 500 are covered by the bait material 450 and thus are not visible through the window 550. However, as the bait material 450 becomes consumed, increasingly more of the cavity surface, bottom surface of the bait cartridge 475, and/or the mesh-like member 500 will become more prominently visible. As such, the user will be able to readily determine, at a glance, if the bright color of the cavity surface, bottom surface of the bait cartridge 475, and/or mesh-like member 500 are visible, thereby indicating the presence of termites and/or other wood-destroying insects in the vicinity. One skilled in the art will appreciate, however, that the same function may be accomplished in other manners. For example, the bait material 450 itself may be brightly colored, while the cavity surface, bottom surface of the bait cartridge 475, and/or the mesh-like member 500 may be colored as the remainder of the housing 100 or in a contrasting color to the bait material 450. As such, the absence of the bright color of the bait material 450 will also indicate whether termites and/or other wood destroying insects are present in the cavity 300.

Many modifications and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing description and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

THAT WHICH IS CLAIMED:

1. A camouflaged termite monitoring device, comprising:
a housing configured as a landscape element and adapted to engage an upper
ground surface, the housing defining a cavity and an opening to the cavity
through a ground-contacting surface of the housing;
5 a perforated bait cartridge configured to fit within the cavity;
a bait material disposed within the bait cartridge and adapted to be attractive to
termites;
a mesh-like member operably engaged with the housing about the ground-
contacting surface so as to cover the opening and to retain the bait
10 cartridge in the cavity, the mesh-like member being further adapted to
allow termites attracted by the bait material to pass therethrough into the
cavity and the bait cartridge and to infiltrate the housing; and
an inspection hatch operably engaged with the housing and configured to allow
visual inspection of the bait cartridge within the cavity from outside the
15 housing, so as to determine whether termites have infiltrated the housing
and consumed the bait material in the bait cartridge, without removing the
housing from engagement with the upper ground surface.
2. A device according to Claim 1 wherein the inspection hatch is configured
20 to be opaque.
3. A device according to Claim 1 wherein at least one of the bait cartridge,
the cavity, and the mesh-like member are configured so as to become increasingly
prominently visible through the inspection hatch as the bait material is consumed.
25
4. A device according to Claim 1 further comprising an anchor member
operably engaged with the housing, the anchor member being adapted to secure the
housing in engagement with the upper ground surface.

5. A device according to Claim 1 wherein the housing, the mesh-like member, the bait cartridge, and the bait material are configured to cooperate to allow the bait material to contact the upper ground surface when the housing is in engagement with the upper ground surface.

5

6. A device according to Claim 1 wherein the bait material is configured to be self-wicking.

7. A device according to Claim 1 further comprising a water reservoir disposed within the housing in operable engagement with the bait material and configured so as to provide substantially continuous wetting of the bait material.

8. A device according to Claim 1 wherein the housing further comprises a first portion, the first portion including the ground-contacting surface and being adapted to engage the upper ground surface, and a second portion cooperating with the first portion to define the cavity, the second portion being separably engaged with the first portion and comprising the inspection hatch.

9. A device according to Claim 8 wherein the second portion is connected to the first portion by a hinge.

10. A method of monitoring for termites at a site, comprising:
engaging a housing configured as a landscape element with an upper ground surface without implanting the housing in the ground, the housing defining a cavity and an opening to the cavity through a ground-contacting surface of the housing, the cavity having a perforated bait cartridge disposed therein, the bait cartridge having a bait material disposed therein and adapted to be attractive to termites, the housing having a mesh-like member operably engaged therewith about the ground-contacting surface so as to cover the opening and to retain the bait cartridge in the cavity, the mesh-like member being further adapted to allow termites attracted by the

bait material to pass therethrough into the cavity and the bait cartridge and to infiltrate the housing; and

inspecting the bait cartridge so as to determine whether termites have infiltrated the housing and consumed the bait material in the bait cartridge, without removing the housing from engagement with the ground, at least one of the bait cartridge, the cavity, and the mesh-like member being configured so as to become increasingly prominently visible through the inspection hatch as the bait material is consumed.

10 11. A method according to Claim 10 further comprising securing the housing in engagement with the upper ground surface with an anchor member operably engaged with the housing.

15 12. A method according to Claim 11 wherein inspecting the bait cartridge further comprises inspecting the bait cartridge through an opaque inspection hatch, operably engaged with the housing and configured to allow visual inspection of the bait cartridge within the cavity from outside the housing, by separating the inspection hatch from the housing.

20 13. A method according to Claim 11 wherein engaging the housing with the upper ground surface further comprises engaging the housing with the upper ground surface such that the bait material is in contact with the upper ground surface through the bait cartridge and the mesh-like member.

14. A method according to Claim 11 further comprising continuously wetting the bait material with a water reservoir disposed within the housing in operable engagement with the bait material.

15. A method according to Claim 10 further comprising reporting a termite presence to a central station if inspection of the bait cartridge reveals that termites have infiltrated the housing.

16. A method according to Claim 15 further comprising dispatching a pest control professional to the site in response to the termite presence reported to the central station.



FIG. 1

2/4




FIG. 2




FIG. 3

3/4




FIG. 4

4/4




FIG. 5A




FIG. 5B

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/EP 03/11825

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 A01M1/20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 A01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/116866 A1 (AESCH HAROLD W ET AL) 29 August 2002 (2002-08-29) paragraph '0016! - paragraph '0017! paragraph '0019! paragraph '0021!; figures ---	1-6, 10-13, 15,16
X	US 2002/134004 A1 (GORDON GLENN) 26 September 2002 (2002-09-26) paragraph '0050! paragraph '0056! - paragraph '0058! paragraph '0067!; figures 1-4,8 ---	1-6, 10-13
A	WO 96 32009 A (FMC CORP) 17 October 1996 (1996-10-17)	1
X	page 2, line 9 - line 23 page 3, line 32 -page 4, line 10; figures 1-4 --- -/-	10,11,13

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

16 February 2004

Date of mailing of the international search report

25/02/2004

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Bunn, D

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 03/11825

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2002/148157 A1 (ROLLINS R RANDALL) 17 October 2002 (2002-10-17) paragraph '0041!; figure 8 -----	1, 10

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/11825

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 2002116866	A1	29-08-2002	US 2002108295 A1	15-08-2002
US 2002134004	A1	26-09-2002	NONE	
WO 9632009	A	17-10-1996	AT 233481 T	15-03-2003
			AU 718879 B2	20-04-2000
			AU 5540696 A	30-10-1996
			BR 9604999 A	02-02-1999
			CA 2216999 A1	17-10-1996
			DE 69626506 D1	10-04-2003
			EP 0820223 A1	28-01-1998
			ES 2194099 T3	16-11-2003
			MD 970325 A	31-07-1999
			NZ 306762 A	29-06-1999
			WO 9632009 A1	17-10-1996
			US 6195934 B1	06-03-2001
			US 5937571 A	17-08-1999
US 2002148157	A1	17-10-2002	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.